

8" (203mm) Temperature & Humidity Chart Recorder



Specifications

Alarm Type: Audio/Visual on High/Low Limits

Ambient Operating RH Conditions : 0-95% RH non-condensing

Ambient Operating Temperature Conditions: 32.0 to 120.0F (0.0 to 50.0C)

Approvals: CE

Battery Backup: Four AA Batteries. Powers unit for up to 3 Days.

Battery Life (Avg): 76 Hours (Back-up Only)

Calibration Options: N100, N300, N400

Channels: CH1: Temperature, CH2: Humidity

Chart Rotation Speed: 24 Hour, 7 Day or 31 Day

Dew Point Accuracy: +/-3.6F from 30.0 to 95.0% RH (Calculated) (+/-2.0C from 30.0 to 95.0% RH (Calculated))

Dew Point Range: 32.0 to 122.0F (0.0 to 50.0C)

Dimensions: 3.1 x 9.2 x 9.2in

Display Dimensions Height: 1.375

Display Dimensions Width: 2.0

Display Resolution: 0.1

Display Type: LCD

Enclosure: Rugged Black ABS Case, Polycarbonate Door, Aluminum Dial

Humidity Accuracy: +/-2.0% RH from 5.0 to 95.0%; +/-2.0% RH from 5.0 to 95.0%

Humidity Range: 0-95% RH non-condensing

Humidity Sensor Type: Field Replaceable

IP Rating: 20

Included Accessories: AC Adapter, Red and Blue Pen, Four AA Batteries, Quick Start Guide and Probe. *Charts sold separately.

Keypad Functions: Power On/Off, Pen Home, Alarm

Mounting Options: Free Standing or Wall Mount (With Keyhole)

Power Cord: 6 ft

Power Source: 120 to 240 VAC, 12 VDC (INTL fittings available); AC Adapter

Power Status Indicator: LED Indicator

Remote Probe Dimensions : Replaceable Sensor houses thermistor and RH sensor in polycarbonate plastic 2.5" x .8" x .5"

Remote Sensor Length: 10 ft (single 10 ft extension cable available without sacrificing accuracy)

Remote Sensor Type: Digital Temperature Sensor - Replaceable

Response Time: 5 Minutes to 63% of Full Scale

Temperature Accuracy: +/-0.8F from 32.0 to 120.0F (+/-0.44C from 0.0 to 50.0C)

Temperature Range: -20.0 to 120.0F (-20.0 to 50.0C); 0.0 to 185.0F; 32.0 to 120.0F (0.0 to 50.0C); 40.0 to 110.0F (5.0 to 40.0C)

Temperature Sensor: Remote Probe - Field Replaceable

Unit Weight: 4.6 lbs

Units/Pkg: 1

Warranty: 12-Month Limited

Calibrations

N100: 1-Point NIST Traceable Calibration

N300: 3-Point NIST Traceable Calibration

N400: 3-Point Ultima NIST A2LA Accredited Calibration

Accessories



R180 - Replacement AC Adapter

AC Adapter for TSB/TWE/TWP Loggers and the KT8/KT6 series.



R066 - Universal Plug Kit for Data Loggers

International Plug Kit for Data Loggers



A062 - AC Adapter Extension Cable 10'

10' Power Extension for R157 AC Adapter



A868 - Sensor Dust Filter

Sensor Dust Filter - prolong the life of your sensor.

Accessories



A896 - Probe Extension Cable
10' Extension Probe for Straight Pre-Calibrated Sensor



R250 - Replaceable Sensor
Straight Temperature/Humidity Replaceable Sensor